

Industrial microcomputer flame sensor with universal signal output and self-checking

Abstract

A flame detection system utilizing microcomputer control of a unique self – checking signal interruption system for checking the status of the sensing tube by employing solid state switches and a balance beam shutter. The microcomputer uses a diode and a solid state relay circuit to generate a compatible signal output to a burner control.

Inventors: Wild; Gary G. (Rockford, IL); Eley; John D. (Beloit, WI)

Assignee: GN Electronics, Inc. (Machesney Park, IL)

References Cited (Related Applications)

U.S. Patent Documents

2911540	Nov., 1959	Powers	250/554.
3742474	Jun., 1973	Muller	340/578
3820097	Jun., 1974	Larson	307/117
4395638	Jul., 1983	Cade	250/554
4520390	May, 1985	Paredes	505/445
4591725	May, 1986	Bryant	250/554
4653998	Mar., 1987	Sohma et al	431/79
4746178	May, 1988	Canty	362/576
4904986	Feb., 1990	Pinkaers	340/578
4965601	Oct., 1990	Canty	396/19
4977418	Dec., 1990	Canty	396/19
5230556	Jul., 1993	Canty	362/562
5245196	Sep., 1993	Cabalfin	250/554
5300836	Apr., 1994	Cha	327/113
5510772	Apr., 1996	Lasenby	340/578
5548277	Aug., 1996	Wild	340/578
5549469	Aug., 1996	Wild	431/79
5952930	Aug., 1999	Umeda et al	340/579
5993194	Nov., 1999	Lemelson et al	431/79

Additional References

"45UV5 self-checking UV scanners", brochure of Fireye, Inc in Derry New Hampshire

"Electronic Flame Supervision", brochure of Pyronics, Inc. in Cleveland, Ohio.